

Alu & Mag Drive Reman



When E-Bikes become Re-Bikes.



Drive Remanufactured

- Up to 33 %* emissions saved compared to new production
- Lower-cost riding with refurbished components
- Safe riding with the same quality standards

Product name	Drive Remanufactured
Part number	Each remanufactured drive variant has its own material number
Weight	Mag 2.9 kg // Alu 3,4 kg
Rated voltage	36 V
Continuous rated power	250 W
Torque	50 – 90 Nm, depending on drive variants

Maximum assistance	280 – 410 %, depending on drive variants
Assistance up to	25 km/h
Walk assist up to	6 km/h
Ingress protection (sealing)	IP56
Available for the following drive variants	$S_{Mag} V / S_{Mag} H / C_{Mag} H / T_{Mag} V / T_{Mag} H$ $S_{Alu} / T_{Alu} / C_{Alu}$

For detailed information, please see the datasheet of the drive variants.

Disclaimer: Details may still be optimized, therefore these are preliminary figures.

*The CO₂ footprint of a remanufactured drive is 1/3 lower compared to new production. CO₂ emissions generated by our own activities (Scope 1 and 2) and in the upstream supply chain (Scope 3 upstream) are considered. Scope 1, 2 and 3 are used in accordance with the Greenhouse Gas Protocol Corporate Accounting and Reporting Standard.

Phone: +49 30 343 498-100 / Fax: +49 30 343 498-122 / E-mail: service.ebike@yamaha-ebike-systems.com